NEW HOT LINKS

ATV ANALOG VIDEO PRODUCTS Quick Reference Guide

ATV RECORDERS

DIGITAL VIDEO RECORDERS (DVR)

CATEGORY	ULTIMATE		VALUE					SPECIALTY
MODEL NUMBERS	FA-HD916	FA-HDX16	VLD904 / VLD908	VLD916	VLDVR4-A	VLDVR8 / 16	VLD4500	DYK14G
VIDEO COMPRESSION	H.264	H.264	H.264	H.264	H.264	H.264	H.264	MPEG4
MAX. RECORD & PLAYBACK RATE	480-ips @ D1 / 960H	480-ips @ D1	120-ips @ D1 / 960H / 240-ips @ D1 / 960H	480-ips @ D1 / 960H	120-ips @ 2CIF	120-ips / 240-ips @ 2CIF	120-ips @ D1	30-ips @ CIF
FILE SIZE (KB)	1 / 2 / 4 / 6 (x2 for 2CIF, x4 for D1)	2 / 4 / 6 / 8 (x2 for 2CIF, x4 for D1)	1 / 2 / 4 / 8 (x2 for 2CIF, x4 for D1)	2 / 4 / 6 / 8 (x2 for 2CIF, x4 for D1)	2 / 4 / 6 / 8 (x2 for 2CIF, x4 for D1)	2 / 4 / 6 / 8 (x2 for 2CIF, x4 for D1)	1 / 2 / 4 / 8 (x2 for 2CIF, x4 for D1)	-
VIDEO INPUTS	16 (looping)	16 (looping)	4 / 8	4 / 8	4	8 / 16	4	1
HDD BAYS & SIZES	2TB up to 9TB (3-HDD slots)	2TB up to 15TB (5-HDD slots)	500GB up to 5TB (1-HDD slot)	1TB up to 10TB (2-HDD slot)	500GB up to 3TB (1-HDD slot)	500GB up to 3TB (8ch, 1-HDD slot) 1TB up to 3TB (16ch, 1-HDD slot)	500GB up to 2TB (1-HDD slot)	4GB SD Card
CONNECTIONS								
HDMI	1	1	1	1	-	-	-	-
VGA	1	2	1	1	1	1	1	-
COMPOSITE	-	2	1	1	1	1	1	1
SPOT MONITOR	1 (Composite)	1 (Composite)	-	-	-	-	-	-
AUDIO INPUTS / OUTPUTS	4 / 1	16 / 1	4 / 1	4 / 1	4 / 1	4 / 1	1 / 1	1 / 1
USB	2 - v 2.0	2 - v 2.0	2 - v 2.0	2 - v 2.0	2 - v 2.0	2 - v 2.0	2 - v 2.0	-
ARCHIVE MEDIA	Internal DVD-RW, iSCSI, eSATA, USB Flash Drive	Internal DVD-RW, iSCSI, eSATA, USB Flash Drive	USB Flash Drive	USB Flash Drive	USB Flash Drive	USB Flash Drive	USB Flash Drive	Upgradable SD Card up to 32GB
ALARM IN / OUT	16 / 2	16 / 4	4 or 8 / 1	16 / 1	4 / 1	8 or 16 / 1	4 / 1	-
ETHERNET	RJ-45 (10/1000 Base-T)	RJ-45 (10/1000 Base-T)	RJ-45 (10/100 Base-T)	RJ-45 (10/100 Base-T)	RJ-45 (10/100 Base-T)	RJ-45 (10/100 Base-T)	RJ-45 (10/100 Base-T)	-
IR REMOTE CONTROL & MOUSE	Yes (included)	Yes (included)	Yes (included)	Yes (included)	Yes (included)	Yes (included)	IR Remote Only	-
RECORD / SEARCH MODES								
RECORD RESOLUTION	480x240 / 960x240 / 960x480	360x240 / 720x240 / 720x480	360x240 to 960x480	360x240 to 960x480	360x240 / 720x240 / 720x480	360x240 / 720x240 / 720x480	360x240 / 720x240 / 720x480	352x240 / 704x480
RECORD MODE	TL, Event, Pre-event (30m), Panic, Text-in	TL, Event, Pre-event (30m), Panic, Text-in	Continuous, Manual, Event, Schedule, Sensor, Alarm	Continuous, Manual, Event, Schedule, Sensor, Alarm	TL, Event, Pre-event (30s), Panic, Text-in	TL, Event, Pre-event (30s), Panic, Text-in	Schedule, Event, Pre-event	Manual, Continuous, Event
SEARCH MODE	D/T, Calendar, Event, Motion, Museum, Text-in	D/T, Calendar, Event, Motion, Museum, Text-in	Date/Time, Event, Time Bar	Date/Time, Event, Time Bar	D/T, Calendar, Event, Motion, Museum, Text-in	D/T, Calendar, Event, Motion, Museum, Text-in	Time, Event	Time, Event
OPERATION								
USER INSTRUCTION MANUAL	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link	Manual Link
# REMOTE CONNECTIONS	2-Admin, 10-Watch, 2-Search	2-Admin, 10-Watch, 2-Search	4	3	2-Admin, 10-Watch, 2-Search	2-Admin, 10-Watch, 2-Search	5	-
# USERS	64 Groups, 256 Users	64 Groups, 256 Users	6 Users, 1 Admin	6 Users, 1 Admin	64 Groups, 256 Users	64 Groups, 256 Users	4 Users, 1 Admin	-
REMOTE DESKTOP	Yes	Yes	-	-	-	-	-	-
REMOTE ACCESSIBILITY	ATVision Pro, Webguard	ATVision Pro, Webguard	ATV SkyVision	ATV SkyVision	ATVision Pro, Webguard	ATVision Pro, Webguard	CMS	-
QUICK SETUP GUIDE	Guide Link	Guide Link	-	-	Guide Link	Guide Link	-	-
REMOTE HEALTHCHECK	-	Yes	-	-	-	-	-	-
MOBILITY SUPPORT	Android, iPhone, iPad	Android, iPhone, iPad	Android, iPhone, iPad	Android, iPhone, iPad	Android, iPhone, iPad	Android, iPhone, iPad	Android, iPhone, iPad	-
ACCESSORIES	XDLBB2 Lock Box; eSATA devices	LB3L Lock Box; eSATA devices	XDLBB2 Lockbox	XDLBB2 Lockbox	LB3S Lock Box	LB3S Lock Box (8ch) / XDLBB2 Lock Box (16ch)	LB3S Lockbox	-

ATV ANALOG CAMERAS

SPECIALTY CAMERAS

CATEGORY	LICENSE PLATE	COVERT			
MODEL NUMBERS	CLP7550I	CH7D37PB(S) CS7D37PB	CT736PB	CM728PB(S)	CXAVW25P
DESCRIPTION	License Plate Capture Camera	Covert Height Strip & Mini Strip, DN	Covert Tower, DN	Covert Mullion, DN	Board Camera, DN, D-WDR
OUTDOOR IP RATING	IP66	-	-	-	-
IMAGE SENSOR	1/3" CCD	1/3" CCD	1/3" CCD	1/3" CCD	1/3" CCD
RESOLUTION	700TVL (BW Only)	700TVL / 750TVL	700TVL / 750TVL	700TVL / 750TVL	600TVL / 650TVL
LENS	5-50mm VF AI	3.7mm	3.6mm	2.8mm	2.5mm
IR LED'S	10 High Power LED's (90ft range outdoor)	-	-	-	-
MIN. SCENE ILLUM. (LUX)	0 (BW IR LED On)	0.1 (Color); 0.04 (BW)	0.1 (Color); 0.04 (BW)	0.1 (Color); 0.04 (BW)	1 (Color); 0.01 (BW)
WDR	-	-	-	-	Digital
DAY/NIGHT	N.A. (BW Only)	Digital	Digital	Digital	Digital
POWER SOURCE & CONSUMPTION	24VAC 750mA (heater on)	12VDC PS incl; 125mA	12VDC PS incl; 130mA	12VDC PS incl; 130mA	12VDC; 120mA
ADDITIONAL FEATURES	External Zoom and Focus Adjustment, Heater, Thru-Mount Wiring	2D-DNR, AGC, SLC, AWB; Gimbal bracket; Adjustable Height & Tilt	2D-DNR; AWB, AGC; Adjustable Height and Tilt; Base mount incl	2D-DNR, AWB, AGC	Mirror Image; Privacy; VMD, 2D-DNR; AWB, Gain, Gimbal bracket incl
ACCESSORIES	A-CM150 Corner Mt; A-CM151 Pole Mt	-	-	-	-
VIDEO CLIP	-	-	Video Link	-	-
USER INSTRUCTION MANUAL	Manual Link	HS Manual Link MS Manual Link	Manual Link	Manual Link	Manual Link

ATV MONITOR

CATEGORY	CCTV MONITOR
	PERFORMANCE
MODEL NUMBERS	MLE800
DESCRIPTION	LCD CCTV Monitor
PANEL SIZE	8"
CASE COLOR	Black
RESOLUTION	800 x 800
PIXEL PITCH	0.2025mm
VIEWING ANGLE LR/UD	140 / 130
BACKLIGHT	LED
ASPECT RATIO	4 x 3
CONTRAST RATIO	500:1
COLOR DEPTH	16.2M
RESPONSE TIME	20mS
BRIGHTNESS	270cd/m2
POWER	<15W
VOLTAGE	12VDC
USER INSTRUCTION MANUAL	Manual Link
INPUTS	
VGA	Yes
BNC / LOOPING	1 / 1

ATV STORAGE

EXTERNAL STORAGE DEVICES

MODEL NUMBERS	(Special Order; Call for Availability)
DESCRIPTION	E-SATA Storage Devices
HDD TRAYS	Hot-Swappable 3.5"
NUMBER OF HDD'S	4 or 5
RAID LEVEL	Pre-configured RAID 5
MAXIMUM CAPACITY	12TB or 15TB (based on 3TB HDD)
AUTO REBUILDING	Yes
HOT-SPARE	Yes
HOST INTERFACE	USB 3.0 & e-SATA
DRIVE INTERFACE	4 (or 5) x 3.5" SATAI / SATAII
POWER SOURCE & CONSUMPTION	115V-230V Switchable; 150W (4-bay), 220W (5-bay)
ADDITIONAL FEATURES	Rack or Desktop model; Power cord, e-SATA cable, USB 3.0 cable incl
USER INSTRUCTION MANUAL	Manual Link

ATVision PRO

ATV SkyVision

Main Number	972.459.8645
Toll Number	888.288.7644
Tech Support	888.288.7644 x4

Paul Lange	603.303.7422	National Sales Manager
Scott Youzva	972.816.5116	Distribution Sales Manager

Regional Sales Managers

Bill O'Day	973.647.2282	Northeast
Jeff Swaim	336.918.6640	South-Central
Todd Dunham	678.372.4365	Southeast
Mike Romeo	972.467.0421	Mid-West
John Jacobsen	503.857.3207	West

NEW HOT LINKS

ATV ANALOG VIDEO PRODUCTS Quick Reference Guide

ATV ANALOG CAMERAS

VANDAL DOMES

ULTIMATE

CATEGORY			
MODEL NUMBERS	CTRT7212W (G) CTRT7550W (G)	CZ7T2812UWCI	VD700WDR
DESCRIPTION	Turret Dome, Sens-Up, TDN, IR, D-WDR	Vandal Dome, Extreme Weatherproof, TDN, D-WDR, IR, Sens-Up	Vandal Dome, TDN, WDR, Sens-Up
OUTDOOR IP RATING	IP66	IP68	IP66
IMAGE SENSOR	1/3" CCD	1/3" CCD	1/3" CCD
RESOLUTION	700TVL / 750TVL	700TVL / 750TVL	700TVL / 750TVL
LENS	2.8-12mm VF AI 5-50mm VF AI	2.8-12mm VF AI	2.8-12mm VF AI
IR LED'S	42 LED's (100ft indoor range 80ft outdoor range)	33 LED's (100ft indoor range, 80ft outdoor)	-
MIN. SCENE ILLUM. (LUX)	0.15 (Color) 0.00002 (BW, IR LED On)	0.1 (Color) 0 (BW, IR LED On)	0.1 (Color) 0.05 (BW)
WDR	Digital	Digital	TRUE
DAY/NIGHT	TRUE	TRUE	TRUE
POWER SOURCE & CONSUMPTION	12VDC/24VAC 600mA / 300mA (IR LED On)	12VDC/24VAC 860mA / 350mA (IR & Heater On)	12VDC/24VAC 300mA / 145mA
ADDITIONAL FEATURES	16x Digital Zoom; VMD, DIS, Privacy, Sens-Up, DNR3, Mirror, BLC, AWB, AGC	Built-in Heater, Mirror Image, Privacy, Digital Zoom, VMD, DIS, 3D-DNR, BLC, AWG, AGC, Sens-Up	BLC, HLC, Sens-Up, VMD, Privacy, AWB, AGC, Digital Zoom, 3D-DNR
ACCESSORIES	TCW2-W(G) Wall Mt, TCADP Adapter Plate; TCP-W(G) Pendant Mt	TCW2-W Wall Mt, TCP-W Pendant Mt	DB243W2 Wall Mt; PDA5W(B) Pendant Mt; VDMWC Wall/Ceiling Mt; CV-FLUSHMT Flush Mt; Heater HT202VK
VIDEO CLIP	Video Link	-	-
USER INSTRUCTION MANUAL	Manual Link	Manual Link	Manual Link

PERFORMANCE

CATEGORY				
MODEL NUMBERS	LV72WI	VDM700DN (6-Pack Available)	CZ6T2812UWC	VD600TDNW
DESCRIPTION	Vandal Dome, TDN, IR, D-WDR	Vandal Mini-Dome, DN	Vandal Dome, Extreme Weatherproof, TDN, D-WDR, Sens-Up	Vandal Dome, TDN, D-WDR
OUTDOOR IP RATING	IP66	IP67	IP68	IP66
IMAGE SENSOR	1/3" CCD	1/3" CCD	1/3" CCD	1/3" CCD
RESOLUTION	700TVL / 750TVL	700TVL / 750TVL	600TVL / 650TVL	600TVL / 650TVL
LENS	2.8-12mm VF AI	3.6mm Fixed	2.8-12mm VF AI	2.8-12mm VF AI
IR LED'S	30 IR LED's (80ft outdoor range, 100ft indoor range); Smart IR Technology	-	-	-
MIN. SCENE ILLUM. (LUX)	0.01 (Color); 0 (BW, IR LED On)	0.05 (Color)	0.15 (Color); 0.15 (BW)	0.14 (Color); 0.03 (BW)
WDR	Digital	-	Digital	Digital
DAY/NIGHT	TRUE	Digital	TRUE	TRUE
POWER SOURCE & CONSUMPTION	12VDC / 24VAC 420mA / 210mA (IR LED On)	12VDC 110mA	12VDC/24VAC 400mA/ 170mA	12VDC / 24VAC 333mA / 167mA
ADDITIONAL FEATURES	Mirror Image; Privacy; VMD, 2D-DNR, BLC, AWB, AGC	2D-DNR	Built-in Heater; Mirror Image, Privacy, Digital Zoom, VMD, DIS, 3D-DNR, BLC, AWG, Gain, Sens-Up	Mirror Image; VMD, Privacy, Digital Zoom, 3D-DNR, BLC, AWB, AGC, DIS
ACCESSORIES	HT202VF Heater; DB243W2(B) Wall Mt; PDA5W(B) Pendant Mt; BTCV5 Smoked Bubble; CV-FLUSHMT Flush Mt; VDMWC Wall/Ceiling Mt; VDSMR Surface Mt Ring	-	TCW2-W Wall Mt, TCP-W Pendant Mt	HT202VF Heater; DB243W2 Wall Mt; PDA5W(B) Pendant Mt; BTCV5 Smoked Bubble; CV-FLUSHMT Flush Mt; VDMWC Wall/Ceiling Mt; VDSMR Surface Mt Ring
VIDEO CLIP	-	-	-	-
USER INSTRUCTION MANUAL	Manual Link	Manual Link	Manual Link	Manual Link

VALUE

CATEGORY	
MODEL NUMBERS	VLVDIR
DESCRIPTION	Vandal Dome, DN
OUTDOOR IP RATING	IP66
IMAGE SENSOR	1/3" CCD
RESOLUTION	540TVL / 590TVL
LENS	3.6mm Fixed
IR LED'S	24 LED's 60ft Range
MIN. SCENE ILLUM. (LUX)	0.4 (Color); 0 (BW, IR LED On)
WDR	-
DAY/NIGHT	Digital
POWER SOURCE & CONSUMPTION	12VDC PS incl; 440mA (IR On)
ADDITIONAL FEATURES	AWB, AGC
ACCESSORIES	-
VIDEO CLIP	-
USER INSTRUCTION MANUAL	Manual Link

BOX

ULTIMATE

CATEGORY	
MODEL NUMBERS	C700TDN
DESCRIPTION	Full body, TDN, D-WDR
OUTDOOR IP RATING	-
IMAGE SENSOR	1/3" CCD
RESOLUTION	700TVL / 750TVL
LENS	C / CS Mount
IR LED'S	-
MIN. SCENE ILLUM. (LUX)	0.15 (Color); 0.01 (BW)
WDR	Digital
DAY/NIGHT	TRUE
POWER SOURCE & CONSUMPTION	12VDC / 24VAC 240mA / 230mA
ADDITIONAL FEATURES	Mirror Image; Privacy; VMD, DIS, 2D-DNR, BLC, WB, AGC
ACCESSORIES	EHWMHB Environmental Hsg / Wall Mt. A-CM150 Corner Mt; A-CM151 Pole Mt; SCV2812ASIR 2.8-12mm lens; SCV55014DC 5-5mm lens
VIDEO CLIP	-
USER INSTRUCTION MANUAL	Manual Link

INTERIOR DOMES

ULTIMATE

CATEGORY	
MODEL NUMBERS	FD700WDR
DESCRIPTION	Interior Dome, TDN, WDR, Sens-Up
OUTDOOR IP RATING	-
IMAGE SENSOR	1/3" CCD
RESOLUTION	700TVL / 750TVL
LENS	2.8-12mm VF AI
IR LED'S	-
MIN. SCENE ILLUM. (LUX)	0.1 (Color) 0.05 (BW)
WDR	TRUE
DAY/NIGHT	TRUE
POWER SOURCE & CONSUMPTION	12VDC/24VAC 300mA / 145mA
ADDITIONAL FEATURES	BLC, HLC, Sens-Up, VMD, Privacy, AWB, AGC, Digital Zoom, 3D-DNR
ACCESSORIES	DB244 Wall Mt; PDA328 Pendant Mt
VIDEO CLIP	-
USER INSTRUCTION MANUAL	Manual Link

PERFORMANCE

CATEGORY			
MODEL NUMBERS	LD72W(I) LD72B(I)	FD600EDN	FD600DNIR
DESCRIPTION	Interior Dome; TDN, D-WDR	Interior Dome; DN, D-WDR	Interior Dome; TDN, IR, D-WDR
OUTDOOR IP RATING	-	-	-
IMAGE SENSOR	1/3" CCD	1/3" CCD	1/3" CCD
RESOLUTION	700TVL / 750TVL	600TVL / 650TVL	600TVL / 650TVL
LENS	2.8-12mm VF AI	4-9mm VF AI	4-9mm VF AI
IR LED'S	IR Model Only: 30 IR LED's (100ft indoor range); Smart IR Technology	-	23 LED's / 100ft range; Smart IR Technology
MIN. SCENE ILLUM. (LUX)	0.1 (Color); 0 (BW, IR LED On)	0.1 (Color); 0.04 (BW)	0.1 (Color); 0 (BW, IR LED On)
WDR	Digital	Digital	Digital
DAY/NIGHT	TRUE	Digital	TRUE
POWER SOURCE & CONSUMPTION	12VDC/24VAC; 166mA / 83mA (non-IR) 420mA / 210mA (IR LED On)	12VDC / 24VAC 375mA / 1.87A	12VDC / 24VAC 208mA / 104mA (IR LED On)
ADDITIONAL FEATURES	Mirror Image; Privacy; Digital Zoom, VMD, DIS, 2D-DNR, BLC, AWB, AGC	Mirror Image; Privacy; VMD, 2D-DNR, BLC, AWB, AGC	Mirror Image; Privacy; VMD, 2D-DNR, BLC, AWB, AGC
ACCESSORIES	DB243W2(B) Wall Mt; PDA5W(B) Pendant Mt; CV-FLUSHMT Flush Mt; VDSMR Surface Mt Ring	DB243W2 Wall Mt; PDA5W(B) Pendant Mt; CV-FLUSHMT Flush Mt	DB243W2 Wall Mt; PDA5W(B) Pendant Mt; CV-FLUSHMT Flush Mt
VIDEO CLIP	-	-	-
USER INSTRUCTION MANUAL	Manual Link	Manual Link	Manual Link

PTZ DOMES

ULTIMATE

CATEGORY	
MODEL NUMBERS	SD536DWA
DESCRIPTION	36x, TDN, WDR, Video Analytics, PTZ Dome
OUTDOOR IP RATING	-
IMAGE SENSOR	1/4" CCD
RESOLUTION	540TVL / 590TVL
LENS	3.4-122.4mm (36x optical zoom)
IR LED'S	-
MIN. SCENE ILLUM. (LUX)	1.4 (Color); 0.01 (BW)
WDR	TRUE
DAY/NIGHT	TRUE
POWER SOURCE & CONSUMPTION	12VDC / 24VAC 1.7A / 833mA
ADDITIONAL FEATURES	12x digital zoom; Privacy; Video Analytics; RS-485; Tours, Auto-Scans, Presets
ACCESSORIES	DB241 Pendant Mt; DB242 Wall Mt; PM304 Parapet Mt; FM-SD1 Flush Mt; DH304-OC Outdoor Environmental Hsg; SDK162J Keyboard
VIDEO CLIP	-
USER INSTRUCTION MANUAL	Manual Link

PERFORMANCE

CATEGORY		
MODEL NUMBERS	SDM722DW	SDM722DWH
DESCRIPTION	Compact 22x PTZ Dome, TDN, WDR	Compact 22x PTZ Dome in Environmental Housing, TDN, WDR
OUTDOOR IP RATING	IP66	IP66
IMAGE SENSOR	1/4" CCD	1/4" CCD
RESOLUTION	700TVL / 750TVL	700TVL / 750TVL
LENS	3.9-85.8mm (22x optical zoom)	3.9-85.8mm (22x optical zoom)
IR LED'S	-	-
MIN. SCENE ILLUM. (LUX)	0.1 (Color); 0.00001 (BW)	0.1 (Color); 0.00001 (BW)
WDR	TRUE	TRUE
DAY/NIGHT	TRUE	TRUE
POWER SOURCE & CONSUMPTION	24VAC; 917mA	24VAC; 917mA
ADDITIONAL FEATURES	16x digital zoom; Heater; RS-485; Tours, Auto-Scans, Presets	16x digital zoom; Heater / Blower; RS-485; Tours, Auto-Scans, Presets
ACCESSORIES	VDMWC2 Ceiling and Wall Mt; DB243W2 Wall Mt; A-PEXM Pendant Mt; A-PFM Flush Mt; A-PPDM Pendant Cap; A-CM150 Corner Mt; A-CM151 Pole Mt; SDK162J Keyboard	DB241 Pendant Mt; DB242 Wall Mt; PM304 Parapet Mt; PB120 Wall Mt/Power Supply; A-CM150 Corner Mt; A-CM151 Pole Mt SDK162J Keyboard
VIDEO CLIP	-	-
USER INSTRUCTION MANUAL	Manual Link	Manual Link

BULLETS

PERFORMANCE

CATEGORY			
MODEL NUMBERS	BHR7550LR	BHR7212MR	BHR7212SR
DESCRIPTION	Bullet, TDN, IR, D-WDR	Bullet, TDN, IR, D-WDR	Bullet, TDN, IR
OUTDOOR IP RATING	IP67	IP67	IP67
IMAGE SENSOR	1/3" CCD	1/3" CCD	1/3" CCD
RESOLUTION	700TVL / 750TVL	700TVL / 750TVL	700TVL / 750TVL
LENS	5-50mm VF AI	2.8-12mm VF AI	2.8-12mm VF AI
IR LED'S	45 LED's / 160ft range Smart IR Technology	45 LED's / 160ft range Smart IR Technology	30 LED's / 80ft range Smart IR Technology
MIN. SCENE ILLUM. (LUX)	0.15 (Color); 0 (BW, IR LED On)	0.15 (Color); 0 (BW, IR LED On)	0.1 (Color); 0 (BW, IR LED On)
WDR	Digital	Digital	-
DAY/NIGHT	TRUE	TRUE	TRUE
POWER SOURCE & CONSUMPTION	12VDC / 24VAC 880mA / 1.56A (IR & Heater On)	12VDC / 24VAC 880mA / 1.56A (IR & Heater On)	12VDC PS incl; 375mA
ADDITIONAL FEATURES	Thru-Mount Wiring; Heater; 2D-DNR, Privacy, Mirror, VMD, BLC, AWB, AGC	Thru-Mount Wiring; Heater; 2D-DNR, Privacy, Mirror, VMD, BLC, AGC, AWB	Thru-Mount Wiring; 2D-DNR, AWB, AGC
ACCESSORIES	A-CM150 Corner Mt; A-CM151 Pole Mt	A-CM150 Corner Mt; A-CM151 Pole Mt	A-CM150 Corner Mt; A-CM151 Pole Mt
VIDEO CLIP	-	-	Video Link
USER INSTRUCTION MANUAL	Manual Link	Manual Link	Manual Link

VALUE

CATEGORY		
MODEL NUMBERS	BSS7550	BSS7212	VLB7IR
DESCRIPTION	Bullet, TDN, IR, D-WDR	Bullet, TDN, IR, D-WDR	Bullet, DN, IR
OUTDOOR IP RATING	IP66	IP66	IP68
IMAGE SENSOR	1/3" CCD	1/3" CCD	1/3" CCD
RESOLUTION	700TVL / 720TVL	700TVL / 720TVL	700TVL / 720TVL
LENS	5-50mm VF AI	2.8-12mm VF AI	3.6mm Fixed
IR LED'S	42 LED's 100ft Range	42 LED's 80ft Range	24 LED's 60ft Range
MIN. SCENE ILLUM. (LUX)	0.01 (Color); 0 (BW, IR LED On)	0.1 (Color); 0.01(BW, IR LED On)	0.01 (Color); 0 (BW, IR LED On)
WDR	Digital	Digital	-
DAY/NIGHT	TRUE	TRUE	Digital
POWER SOURCE & CONSUMPTION	12VDC / 24VAC 650mA / 710mA	12VDC / 24VAC 650mA / 710mA	12VDC PS incl; 340mA
ADDITIONAL FEATURES	Thru-Mount Wiring; 2D-DNR, Privacy, VMD, BLC, AGC	Thru-Mount Wiring; 2D-DNR, Privacy, VMD, BLC, AGC	Thru-Mount Wiring; AWB, AGC
ACCESSORIES	A-CM150 Corner Mt; A-CM151 Pole Mt	A-CM150 Corner Mt; A-CM151 Pole Mt	A-CM150 Corner Mt; A-CM151 Pole Mt
VIDEO CLIP	-	-	-
USER INSTRUCTION MANUAL	Manual Link	Manual Link	Manual Link